


KV710X




VSM NON-WOVEN (AO/SIC)

Grain type	Aluminium oxide/ Silicon carbide
Bonding	Full-resin bonded
Colour	Coarse = brown (AO) Medium = red (AO) Very fine = blue (AO) Ultra fine = grey (SIC)
Backing	X-Polyester
Production width	1,000 mm

Materials



Features



Surface conditioning material with optimised, open fibre structure, without any inclusions or islands of resin. This non-woven abrasive has significantly reduced clogging; also when grinding non-ferrous metals. KV710X ensures a consistent scratch pattern throughout its entire, long service life. The backing is soft and flexible enough to adapt to the contours of the workpiece

AO = aluminium oxide SIC = silicon carbide

Fineness range:¹⁾



Benefits

- > No clogging or smearing, even with non-ferrous metals
- > Homogeneous, open texture without any inclusions or lumps of resin
- > Low-stretch backing: Comparatively soft and flexible enough to adapt to the contours of the workpiece
- > Consistent scratch pattern
- > Very high stock removal
- > Very long service life
- > No tempering colors

VSM · Vereinigte Schmirgel- und Maschinen-Fabriken AG
 Siegmundstraße 17 · 30165 Hanover · Germany
 T +49 511 3526 479 · F +49 511 3521 315
 sales@vsmabrasives.com · www.vsmabrasives.com



¹⁾ Further grit sizes upon request. Subject to technical changes.