

AF890





VSM ACTIROX




Grain type	Ceramic
Bonding	Full-resin bonded
Colour	Petrol
Backing	Vulcanised fibre
Production width	1,470 mm

Materials




Features



ACTIROX

The geometrically shaped ceramic grain generates maximum stock removal when machining superalloys and stainless steel. A fast cut and an extremely long service life lead to a significant increase in productivity. The additional grinding-active TOP SIZE layer reduces the temperature in the contact area.


Grit sizes:



Benefits

- > Maximum stock removal thanks to geometrically shaped ceramic grain leads to a reduction in operating costs
- > More than twice as much stock removal compared to conventional ceramic grain abrasives
- > Increase in productivity: More workpieces per unit of time due to fast cutting
- > Extremely stable dimensions and a durable vulcanized backing satisfy the highest safety requirements
- > The tailored and extremely hard back-up pad *VSM TURBO PAD 3* leads to a further increase in stock removal
- > Cool grinding processes and extended service lives thanks to the additional grinding-active layer VSM TOP SIZE

Grain technology



VSM • Vereinigte Schmirgel- und Maschinen-Fabriken AG

Siegmundstraße 17 · 30165 Hannover · Germany
T +49 511 3526 0 · F +49 511 3521 315
sales@vsmabrasives.com · www.vsmabrasives.com

